

Comant CI 105

TRANSPONDER / ADS-B OUT / DME

CI 105 ANTENNA

Comant's two-internal-hole-stud-mount style blade transponder antenna with BNC port. Frequency range supports ADS-B Out and DME applications. Suitable for either top or bottom mounting with light fixed-wing single-engine / multi-engine and helicopter aircraft.

APPLICATIONS

Light Fixed-Wing Single-Engine
Light Fixed-Wing Multi-Engine
Helicopter

Warranty: 1 year

Always consult your installation shop for best application. See full disclaimer (Page 7) for more information

FREQUENCIES COVERED

960-1220 MHz

(L Band - XPDR / ADS-B Out / DME)

SPECIFICATIONS

Electrical

Frequency	960-1220 MHz
VSWR	1.5:1 Max 960-1220 MHz 1.3:1 Max 1025-1150 MHz
Polarization	Vertical
Radiation Pattern	Equivalent to a 1/4 wave stub

Impedance RF	50 Ohms
Resistance DC	Open Circuit
Power RF	2.5 KW Peak

Mechanical

Weight	0.24 lb.
Height	3.23 in.
Finish	Glossy White
Connector	BNC (female)

Environmental

Temperature	-55C to +85C
Altitude	70,000 ft.

Federal Specifications

FAA TSO	C66b, C74c
RTCA Environmental	DO-160C

Gasket	B10505
---------------	--------

