



INSTALLATION DRAWING

REVISIONS		CONTRACT NO.	
LTR	DESCRIPTION	DATE	APPROVAL
G	REDRAWN, REF ECN NO. 03-102	05/02/03	DH 05/08/03
H	REF ECN 15-010	04/14/15	DH 04/21/15
J	REF ECN 16-029	06/20/16	DH 06/21/16

  

UNLESS OTHERWISE SPECIFIED		APPROVALS		DATE	
DIMENSIONS ARE IN INCHES		DRAWN	H. NGUYEN	05/02/03	
DECIMALS - XX + 010 XXX ± .005		CHECK	J. GOMEZ	05/08/03	
FRACTIONS - 1/16 ANGLES ± 1°		ENGR	D. HOLLOWAY	05/08/03	
MACHINE FINISH 125√ PER ANSI-B46.1		OC	P. BOSNEANU	05/08/03	
REMOVE BURRS AND SHARP EDGES 0.015 MAX		APPD	D. HOLLOWAY	05/08/03	
MEET DIMENSIONS BEFORE PLATING					
DIMENSIONS ARE PER ASME Y14.3M					

  

DO NOT SCALE DRAWING		SCALE: 1:1	
ASSY DWG. C.10601		CAD FILE: --	SHEET: 1 OF 1

NOTES: UNLESS OTHERWISE SPECIFIED

- RF CHARACTERISTICS : 450 TO 470 MHZ  
 FREQUENCY : 1.7 :1 MAX.  
 VSWR : VERTICAL  
 POLARIZATION : TYPICAL OF A 1/4 WAVE STUB  
 RADIATION PATTERN : 50 WATTS AVERAGE
- FINISH : TIN-NICKEL ALLOY
- WEIGHT : .18 LBS
- BNC CONNECTOR PICTORIALLY SHOWN
- SPEED RATING : 250 KNOTS TAS