

Comant CI 158C

VHF NAVIGATION VOR / LOC / GS

CI 158C ANTENNA

Comant's two-through-hole-mount style V dipole VOR / LOC / GS antenna with BNC port. Single navigation output, refer to Comant's signal duplexers to achieve desired avionics signal input. Designed with detachable radiator elements. Suitable for mounting on the aircraft vertical stabilizer with light fixed-wing single-engine / multi-engine aircraft.

Not for helicopter installation.

APPLICATIONS

Light Fixed-Wing Single-Engine
Light Fixed-Wing Multi-Engine
Warranty: 1 year

Always consult your installation shop for best application. See full disclaimer (Page 7) for more information.

FREQUENCIES COVERED

108 - 118 MHz (VHF - VOR / LOC)
329 - 335 MHz (UHF - GS)

SPECIFICATIONS

Electrical

Frequency	108-118 MHz (VOR/LOC) 329-335 MHz (GS)
VSWR	3.0:1 Max 108-118 MHz (VOR/LOC) 3.0:1 Max 329-335 MHz (GS)

Polarization	Horizontal
Radiation Pattern	Dipole
Impedance RF	50 Ohms Nominal
Power RF	Receive Only

Mechanical

Weight	0.50 lb.
Height	7/16 in.
Finish	Black housing / Stainless steel whips
Connector	BNC

Environmental

Temperature	-55C to +85C
Altitude	25,000 ft.

Federal Specifications

FAA TSO	C34c, C36c, C40a
RTCA MOPS	DO-192, DO-195, DO-196
RTCA Environmental	DO-160

