

Comant CI 2680-200

COMDAT® VHF COMMUNICATION / GPS NON-WAAS NAVIGATION

CI 2680-200 ANTENNA

Comant's ComDat® four-through-hole-mount style blade VHF / GPS non-WAAS antenna with BNC / TNC ports. This antenna covers both VHF communication and GPS frequencies. GPS C144 certified for class 1 LNAV approaches (lateral navigation only). Designed to be used with 27 dB gain GPS panel mount systems. Suitable for top mounting with both light and heavy fixed-wing single-engine / multi-engine and business jet aircraft.

GPS portion not compatible with most GPS hand held receiver systems.

APPLICATIONS

Light Fixed-Wing Single-Engine
Light Fixed-Wing Multi-Engine
Heavy Fixed-Wing Single-Engine
Heavy Fixed-Wing Multi-Engine
Business Jets

Warranty: 1 year

Always consult your installation shop for best application. See full disclaimer (Page 7) for more information.

FREQUENCIES COVERED

118 - 137 MHz (VHF - Comm)
1575.42 MHz (L1 Band - GPS)
Nominal 27 dB Gain

SPECIFICATIONS

VHF Specifications

Frequency	118-137 MHz
VSWR	2.9:1 Max
Polarization	Vertical
Radiation Pattern	Omnidirectional
Impedance	50 Ohms
Power Rating	50 watts

GPS Preamplifier Specs

Frequency	1575.42 +/-3 MHz
VSWR	1.5:1 Max
Polarization	RHCP
Radiation Pattern	Hemispherical
Impedance	50 Ohms
Gain	26.5 - 31.5 dB
DC Voltage	4 - 24 VDC
DC Curr. Min/Max	25 mA / 40 mA
Noise	3.8 dB Max

Mechanical / Environmental

Weight	1.25 lbs.
RTCA Env. / TSO	DO-160D / C37d, C38d, C144
Connectors	VHF - BNC / GPS - TNC

