

Comant CI 419-200

GPS WAAS NAVIGATION

CI 419-200 ANTENNA

Comant's four-through-hole-mount style teardrop GPS WAAS antenna with TNC ports. GPS C190 certified class 3 LPV precision approaches. Designed to be used with 27 dB gain GPS panel mount systems. Suitable for top mounting for both light and heavy fixed-wing single-engine / multi-engine, and business jet aircraft.

GPS portion not compatible with most GPS hand held receiver systems.

APPLICATIONS

Light Fixed-Wing Single-Engine
Light Fixed-Wing Multi-Engine
Heavy Fixed-Wing Single-Engine
Heavy Fixed-Wing Multi-Engine
Business Jet

Warranty: 1 year

Always consult your installation shop for best application. See full disclaimer (Page 7) for more information.

FREQUENCIES COVERED

1575.42 MHz (L1 Band- GPS)

Nominal 27 dB Gain

SPECIFICATIONS

GPS Preamplifier Characteristics

Frequency	1575.42 +/- 10.23 MHz
VSWR	1.5:1 Max
Polarization	RHCP
Radiation Pattern	Hemispherical
Output Impedance	50 Ohms
Gain @ 1575.42 MHz	26.5 Min / 32.5 Max dB
DC Voltage	4 to 24 VDC
DC Current	40 mA Typical / 60 mA Max
Noise Figure	2.5 dB
G/T Ratio @ 5° Elevation	>/= 31.6 dBK

Mechanical

Weight	5.0 oz.
Finish	Glossy White
Connector	TNC (Female)

Environmental

RTCA Env.	DO-160E
-----------	---------

Federal Specifications

TSO	C190
-----	------

