


REVISIONS		
LTR	DESCRIPTION	DATE
C	REF ECN 02-359	HN 12/16/02
D	REF ECN 05-41	HN 02/18/05
E	REF ECN 05-176	HN 08/09/05
F	REF ECN 08-095	MN 11/11/08
G	REF ECN 20-014	RM 2/25/20
H	REF ECN 22-091	RM 5/23/22
J	REF ECN 22-136	RM 7/21/22

**NOTES:**

- 1.0 ACTIVE & PASSIVE ANTENNA CHARACTERISTICS
  - 1.1 FREQUENCY \_\_\_\_\_ 2332.5 TO 2345.0 MHz
  - 1.2 VSWR \_\_\_\_\_ 1.5:1 MAX.
  - 1.3 POLARIZATION \_\_\_\_\_ LEFT HAND CIRCULAR
  - 1.4 RADIATION PATTERN \_\_\_\_\_ HEMISPHERICAL
  - 1.5 IMPEDANCE \_\_\_\_\_ 50 OHMS OUTPUT (NOMINAL)
  - 1.6 GAIN (MEASURED ON 4° CIRCULAR GROUND PLANE): 4 dBi ± 1 dB NOM. ZENITH.
- 2.0 AMPLIFIER CHARACTERISTICS ACTIVE ANTENNA
  - 2.1 GAIN \_\_\_\_\_ 26 TO 30 dB
  - 2.2 D.C. VOLTAGE \_\_\_\_\_ 4.7 VOLTS TYP. / 6.5 VOLTS MAX.
  - 2.3 D.C. CURRENT \_\_\_\_\_ 45 mA TYPICAL / 65 mA MAX.
  - 2.4 NOISE FIGURE \_\_\_\_\_ 1.1 dB (TYP.)
  - 2.5 OUT OF BAND FILTER ATTENUATION: 25 dB MIN. @ FC ± 220 MHz
  - 3.0 WEIGHT: 4.2 OZ MAX.
  - 4.0 SPEED RATING: 600 KNOTS
  - 5.0 RTCA DO-160 ENV. CAT.: [F]SXB[BT]C[R]X[R]FXSXXZ[UU]J[M]K[XE]2[H]B[CA]
  - 6.0 HOUSING: VALOX DR-48, 15% GLASS.
  - 7.0 A42042 INSTALLATION INSTRUCTIONS SUPPLIED WITH ANTENNA.
  - 8.0 PLACE LABEL BELOW REFERENCE LINE.

ALL INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF Comant Industries, Inc. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF Comant Industries, Inc. IS PROHIBITED.



ASSY. DWG. C42001

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON DECIMALS .XX ± .03 .XXX ± .010 FRACTIONS ± 1/16 ANGLES ± 1° MACHINE FINISH 125✓ PER ANSI-B46.1 REMOVE BURRS AND SHARP EDGES .015 MAX MEET DIMENSIONS BEFORE PLATING DIMENSIONS ARE PER ASME Y14.5M		CONTRACT NO.	
MATERIAL:		APPROVALS	DATE
DO NOT SCALE DRAWING		DRAWN H. NGUYEN	10/21/02
		CHECK J. GOMEZ	10/21/02
		ENGR D. HOLLOWAY	10/21/02
		QC P. BOSNEANU	10/21/02
		APPD D. HOLLOWAY	10/21/02
		Comant Industries, inc.	
		ANTENNA-XM SATELLITE	
DWG. NO. C 51351	CODE IDENT C 51351	DWG. NO. CI 420-1	REV. J
SCALE: 1:1	CAD FILE: --	SHEET: 1 OF 1	