

Specification Sheet

Part Number: T50R9M4



Cable Tie, 8" Long, UL Rated, 50lb Tensile Strength, PA66, Natural, 1000/pkg

Article Number	111-04862
Type	T50R
Color	Natural (NA)
Features & Benefits	• Engineered and manufactured for maximum performance and quality. • Made from 100% high-quality plastic to ensure efficient recycling. • Inside serration for a strong grip onto bundles. • Easy application either manually or with a tensioning tool. • Bent tail allows for simpler insertion.
Quantity Per	bag
Product Description	T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

Short Description	Cable Tie, 8" Long, UL Rated, 50lb Tensile Strength, PA66, Natural, 1000/pkg
Global Part Name	T50R-PA66-NA
Minimum Tensile Strength (Imperial)	50.0
Minimum Tensile Strength (Metric)	225.0
Length L (Imperial)	8.0
Length L (Metric)	203.2
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.18
Width W (Metric)	4.6
Bundle Diameter Min (Imperial)	0.06
Bundle Diameter Min (Metric)	1.5
Bundle Diameter Max (Imperial)	1.97
Bundle Diameter Max (Metric)	50.0
Thickness T (Metric)	1.2

Material	Polyamide 6.6 (PA66)		
Material Shortcut	PA66		
US MIL SPEC	MS3367-1-9, Class 1		
SAE-AS33671			
Flammability			
UL 94 V2			Halogen free
Yes			Operating Temperature (Metric)
-40°F to +185°F (-40°C to +85°C)			ROHS Complaint
Yes			Certification/Specification WEB
CAGE Code 53421 Bundesamt für Wehrtechnik VG 95387 Part 4 Edition: 2008-12 IEC 62275 (2006-10)			UL Recognized (US)
Yes			UL Listed (US and Canada)
Yes			UL Recognized (US and Canada)
Yes			UL Listed (US
Yes			
Package Quantity(Imperial)	1000		
Package Quantity (Metric)	1000		

Customs Number

3926909988